Text: 709X Dorn 100 mm, Stulp 20 mm, PZ, ohne Panik

1.1. **effeff security lock**

solenoid
self-locking with special latchbolt and deadbolt;

high security:
side load withstands lateral forces: 10.000 N
hardened bolt
mechanical processing between special latchbolt and control-latchbolt
for euro profile cylinder,
with electrically controlled
automatic relocking;
monitoring contacts for:
- bolt in
- bolt out
- trigger bolt in;
- inside door handle,
- sabotage line
- cylinder contact
max. power - handling capacity of the micro switches:
24 V DC / 200 mA
cam position of the profile cylinder: max. 45°;
adjustability:
fail locked or fail unlocked version, DIN-direction,

for security fittings (handles on both sides)
with non-splitted handle pin (9 mm);
lock dimensions: 168,5 x 133 x 16,5 mm,
face plate: 235 x 20 x 3 mm,
bolt throw: 20 mm
handle follower: 9 mm
backset: 100 mm
center distance: 72 mm (Euro cylinder)
nominal voltage: 12 V - 24 V DC +15 % / -10 %;
480 - 240 mA;
the power supply must be a stabilized DC voltage;
DIN left / DIN right
Only for the face plate of 20 mm

order-no. (DIN left): effeff 709X901PZX--G44
order-no. (DIN right): effeff 709X901PZX--G45

1 pce. _____

1.2. **effeff flanged face plate**

face plate: 232 x 32 x 3 mm;
chromed;
universal DIN left und right useable

order-no.: effeff Z09XSBL-04----1

1 pce. _____

Further striking plates variants find you in our safety lock catalog!

1.3. **effeff connecting cable**

16-pole;
for security lock 409, 509, 709;
with conector plug on one site;
length: approx. 10 m

order-no.: effeff Z09XKAB--------

1 pce. _____

for the direct transfer of current from the door frame to the door

1.4. **effeff bridging cable**

for surface mounting,
made of nickel-plated brass,
with fixing lugs for screw mounting
to door frame and door,
spiral hose: I.D. = 7
length: 30 cm

order-no.: effeff 10318-30-----00

1 pce. _____

1.5. **effeff bridging cable**

for concealed mounting,
installation either in the door frame or the door,
with single-side flush mounting tray,
cable thickness: 7 mm
(without protection socket 9 mm),
dimensions flush mounting tray
(w x h x d): 24 x 519 x 49,5 mm

order-no.: effeff 10312-20-----00

1 pce. _____

Further cable connector models find you in our safety lock catalog!