

---

**Text:**

---

**1.1. effeff 809-14 security lock**

solenoid  
with latchbolt and self-locking deadbolt;  
for euro profile cylinder,  
fail locked version with electrically controlled  
inside and outside door handle;  
coupling coil currentless: inside and outside door handle is not coupled (free-wheeling),  
coupling coil with current: inside and outside door handle is coupled;  
automatic relocking;  
four potential-free change-over contacts in order to control:  
- profile cylinder,  
- lock bolt position,  
- handle,  
- coupled handle;  
max. power - handling capacity of the micro switches:  
25 V DC / 1 A  
cam position of the profile cylinder: max. 30 °, bottom, left or right;  
for security fittings (handles on both sides)  
with non-splitted handle pin (9 mm);  
dimensions:  
lock: 257 x 50,5 x 20,5 mm,  
faceplate: 300 x 24 x 3 mm,  
bolt throw: 20 mm,  
handle follower: 9 mm,  
backset: 35 mm,  
center distance: 92 mm (Euro cylinder),  
with fourteen-pol snap-in pin;  
nominal voltage: 24 V DC 100 % ED, 120 mA  
used a power supply with stabilised voltage ;  
Please state the required version:  
DIN left / DIN right

order-no. (DIN left): effeff 809-14D92-35F44  
order-no. (DIN right): effeff 809-14D92-35F45

1 pce. \_\_\_\_\_

**1.2. effeff striking plate**

for security locks model 509 and 809;  
dimensions: 235 x 24 x 3 mm;  
radius: 10 mm;  
in stainless steel;  
suitable for DIN left or right

---

order-no.: effeff 809.000098 35

1 pce. \_\_\_\_\_

**Further striking plates variants find you in our safety lock catalog!**

### 1.3. effeff connecting cable

fourteen-pin;  
for model 809:  
backset 35 / 40 mm;  
with snap-in pin;  
length: approx. 9,5 m

order-no.: effeff 809ZBKAB04---00

1 pce. \_\_\_\_\_

**for the direct transfer of current from the door frame to the door**

### 1.4. effeff bridging cable

for surface mounting,  
made of nickel-plated brass,  
with fixing lugs for screw mounting  
to door frame and door,  
spiral hose: I.D. = 7  
length: 30 cm

order-no.: effeff 10318-30-----00

1 pce. \_\_\_\_\_

### 1.5. effeff bridging cable

for concealed mounting,  
installation either in the door frame or the door,  
with single-side flush mounting tray,  
cable thickness: 7 mm  
(without protection socket 9 mm),  
dimensions flush mounting tray  
(w x h x d): 24 x 519 x 49,5 mm

order-no.: effeff 10312-20-----00

1 pce. \_\_\_\_\_

---

**Further cable connector models find you in our safety lock catalog!**