

### **1.1. effeff 809M14 security lock**

solenoid

with latchbolt and self-locking deadbolt;

for euro profile cylinder,

fail locked version with electrically controlled

inside and outside door handle;

coupling coil currentless: inside and outside door handle is not coupled (free-wheeling),

coupling coil with current: inside and outside door handle is coupled;

automatic relocking;

four potential-free change-over contacts in order to control:

- profile cylinder,

- lock bolt position,

- handle,

- coupled handle;

max. power - handling capacity of the micro switches:

25 V DC / 1 A

cam position of the profile cylinder: max. 30 °, bottom, left or right;

for security fittings (handles on both sides)

with non-splitted handle pin (9 mm);

dimensions:

lock: 169 x 106 x 18 mm,

faceplate: 235 x 20 x 3 mm,

(also 24 mm wide available),

bolt throw: 20 mm,

handle follower: 9 mm,

backset: 65 mm,

center distance: 72 mm (Euro cylinder);

nominal voltage: 24 V DC 100 % ED, 120 mA

used a power supply with stabilised voltage ;

Please state the required version:

DIN left / DIN right

order-no. (DIN left): effeff 809M14-72B65F44

order-no. (DIN right): effeff 809M14-72B65F45

1 pce. \_\_\_\_\_

### **1.2. effeff striking plate**

for security locks model 509 and 809;

dimensions: 235 x 20 x 3 mm;

radius: 10 mm;

in stainless steel;

suitable for DIN left or right

---

order-no.: effeff 809.000050 35

1 pce. \_\_\_\_\_

**Further striking plates variants find you in our safety lock catalog!**

### 1.3. effeff connecting cable

fourteen-pin;  
for model 809:  
backset 60 / 65 mm;  
length: approx. 10 m

order-no.: effeff 809ZBKAB06---00

1 pce. \_\_\_\_\_

**for the direct transfer of current from the door frame to the door**

### 1.4. effeff bridging cable

for surface mounting,  
made of nickel-plated brass,  
with fixing lugs for screw mounting  
to door frame and door,  
spiral hose: I.D. = 7  
length: 30 cm

order-no.: effeff 10318-30-----00

1 pce. \_\_\_\_\_

### 1.5. effeff bridging cable

for concealed mounting,  
installation either in the door frame or the door,  
with single-side flush mounting tray,  
cable thickness: 7 mm  
(without protection socket 9 mm),  
dimensions flush mounting tray  
(w x h x d): 24 x 519 x 49,5 mm

order-no.: effeff 10312-20-----00

1 pce. \_\_\_\_\_

**Further cable connector models find you in our safety lock catalog!**

---

