

1.1. effeff 709X security lock

solenoid
self-locking with special latchbolt and deadbolt;

european certificate of conformity 0432-BPR-0001
for the harmonized standard EN 179
classification: 37611342A ;

european certificate of conformity 0432-BPR-0017
for the harmonized standard EN 1125
classification: 37611321/2A ;
for euro profile cylinder,
integrated anti-panic function via inside door handle;
with electrically controlled outside door handle;
automatic relocking;
monitoring contacts for:
- bolt in
- bolt out
- trigger bolt in;
- inside door handle,
- sabotage line
- cylinder contact
max. power - handling capacity of the micro switches:
24 V DC / 200 mA
cam position of the profile cylinder: max. 45°;
adjustability:
fail locked or fail unlocked version, panic - side,
DIN-direction,

for security fittings (handles on both sides)
with splitted handle pin (9 mm);
lock dimensions: 254 x 55 x 20,5 mm,
face plate: 300 x 24 x 3 mm,
bolt throw: 20 mm
handle follower: 9 mm
backset: 40 mm
center distance: 92 mm (Euro cylinder)
nominal voltage: 12 V - 24 V DC +15 % / -10 %;
480 - 240 mA;
the power supply must be a stabilized DC voltage;
right-/left-handed

order-no.: effeff 709X302PZ---G41

1 pce. _____

1.2. effeff flanged face plate

face plate: 232 x 32 x 3 mm;
chromed;
universal DIN left und right useable

order-no.: effeff Z09XSBL-04----1

1 pce. _____

Further striking plates variants find you in our safety lock catalog!

1.3. effeff connecting cable

16-pole;
for security lock 409, 509, 709;
with conector plug on one site;
length: approx. 10 m

order-no.: effeff Z09XKAB-----

1 pce. _____

for the direct transfer of current from the door frame to the door

1.4. effeff bridging cable

for surface mounting,
made of nickel-plated brass,
with fixing lugs for screw mounting
to door frame and door,
spiral hose: I.D. = 7
length: 30 cm

order-no.: effeff 10318-30-----00

1 pce. _____

1.5. effeff bridging cable

for concealed mounting,
installation either in the door frame or the door,
with single-side flush mounting tray,
cable thickness: 7 mm
(without protection socket 9 mm),
dimensions flush mounting tray

(w x h x d): 24 x 519 x 49,5 mm

order-no.: effeff 10312-20-----00

1 pce. _____

Further cable connector models find you in our safety lock catalog!