

Text: 709X Dorn 40 mm, Stulp 24 mm, PZ, ohne Panik

1.1. effeff 709X security lock

solenoid
self-locking with special latchbolt and deadbolt;

high security:

side load withstands lateral forces: 10.000 N

hardened bolt

mechanical processing between special latchbolt and control-latchbolt

for euro profile cylinder,

with electrically controlled

automatic relocking;

monitoring contacts for:

- bolt in
- bolt out
- trigger bolt in;
- inside door handle,
- sabotage line
- cylinder contact

max. power - handling capacity of the micro switches:

24 V DC / 200 mA

cam position of the profile cylinder: max. 45°;

adjustability:

fail locked or fail unlocked version, DIN-direction,

for security fittings (handles on both sides)

with non-splitted handle pin (9 mm);

lock dimensions: 236 x 62,5 x 19 mm,

face plate: 300 x 24 x 3 mm,,

bolt throw: 20 mm

handle follower: 9 mm

backset: 45 mm

center distance: 92 mm (Euro cylinder)

nominal voltage: 12 V - 24 V DC +15 % / -10 %;

480 - 240 mA;

the power supply must be a stabilized DC voltage;

right-/left-handed

order-no.: effeff 709X302PZX--G41

1 pce. _____



1.2. effeff flanged face plate

face plate: 232 x 32 x 3 mm;

chromed;

universal DIN left und right useable

order-no.: effeff Z09XSBL-04----1

1 pce. _____

Further striking plates variants find you in our safety lock catalog!

1.3. effeff connecting cable

16-pole;
for security lock 409, 509, 709;
with conector plug on one site;
length: approx. 10 m

order-no.: effeff Z09XKAB-----

1 pce. _____

for the direct transfer of current from the door frame to the door

1.4. effeff bridging cable

for surface mounting,
made of nickel-plated brass,
with fixing lugs for screw mounting
to door frame and door,
spiral hose: I.D. = 7
length: 30 cm

order-no.: effeff 10318-30-----00

1 pce. _____

1.5. effeff bridging cable

for concealed mounting,
installation either in the door frame or the door,
with single-side flush mounting tray,
cable thickness: 7 mm
(without protection socket 9 mm),
dimensions flush mounting tray
(w x h x d): 24 x 519 x 49,5 mm

order-no.: effeff 10312-20-----00

1 pce. _____

Further cable connector models find you in our safety lock catalog!