

**1.1. effeff 709X security lock**

solenoid  
self-locking with special latchbolt and deadbolt;

european certificate of conformity 0432-BPR-0001  
for the harmonized standard EN 179  
classification: 37611342A ;

european certificate of conformity 0432-BPR-0017  
for the harmonized standard EN 1125  
classification: 37611321/2A ;  
for euro profile cylinder,  
integrated anti-panic function via inside door handle;  
with electrically controlled outside door handle;  
automatic relocking;  
monitoring contacts for:  
- bolt in  
- bolt out  
- trigger bolt in;  
- inside door handle,  
- sabotage line  
- cylinder contact  
max. power - handling capacity of the micro switches:  
24 V DC / 200 mA  
cam position of the profile cylinder: max. 45°;  
adjustability:  
fail locked or fail unlocked version, panic - side,  
DIN-direction,

for security fittings (handles on both sides)  
with splitted handle pin (9 mm);  
lock dimensions: 168,5 x 93 x 16,5 mm,  
face plate: 235 x 24 x 3 mm,  
bolt throw: 20 mm  
handle follower: 9 mm  
backset: 60 mm  
center distance: 72 mm (Euro cylinder)  
nominal voltage: 12 V - 24 V DC +15 % / -10 %;  
480 - 240 mA;  
the power supply must be a stabilized DC voltage;  
right-/left-handed

order-no.: effeff 709X602PZ---G41

1 pce. \_\_\_\_\_

---

## 1.2. effeff flanged face plate

face plate: 232 x 32 x 3 mm;  
chromed;  
universal DIN left und right useable

order-no.: effeff Z09XSBL-04----1

1 pce. \_\_\_\_\_

**Further striking plates variants find you in our safety lock catalog!**

## 1.3. effeff connecting cable

16-pole;  
for security lock 409, 509, 709;  
with conector plug on one site;  
length: approx. 10 m

order-no.: effeff Z09XKAB-----

1 pce. \_\_\_\_\_

**for the direct transfer of current from the door frame to the door**

## 1.4. effeff bridging cable

for surface mounting,  
made of nickel-plated brass,  
with fixing lugs for screw mounting  
to door frame and door,  
spiral hose: I.D. = 7  
length: 30 cm

order-no.: effeff 10318-30-----00

1 pce. \_\_\_\_\_

## 1.5. effeff bridging cable

for concealed mounting,  
installation either in the door frame or the door,  
with single-side flush mounting tray,  
cable thickness: 7 mm  
(without protection socket 9 mm),  
dimensions flush mounting tray

---

(w x h x d): 24 x 519 x 49,5 mm

order-no.: effeff 10312-20-----00

1 pce. \_\_\_\_\_

**Further cable connector models find you in our safety lock catalog!**