

---

**Text:**

---

### 1.1. effeff 819E32 security lock

electric- multi point lock  
self-locking with latchbolt and lock bolt;  
with two additional deadbolt;  
european certificate of conformity 0432-BPR-0017  
for the harmonized standard EN 1125  
classification: 37601321A;

for euro profile cylinder,  
integrated panic function via inside door handle;  
fail unlocked version with electrically controlled outside door handle;  
coupling coil currentless: outside door handle is coupled;  
coupling coil with current: outside door handle is not coupled  
(free-wheeling),  
automatic relocking;  
four potential-free change-over contacts in order to control:  
- profile cylinder,  
- lock bolt position,  
- inside handle,  
- outside handle;  
max. power - handling capacity of the micro switches:  
25 V DC / 1 A  
cam position of the profile cylinder: max. 30 °, bottom, left or right;  
for security fittings (handles on both sides)  
with a splitted handle pin (9 mm);  
dimensions:  
lock: 257 x 55,5 x 21 mm,  
faceplate: 1760 x 24 x 6 mm  
bolt throw: 20 mm,  
handle follower: 9 mm,  
backset: 40 mm,  
center distance: 92 mm (Euro cylinder),  
with fourteen-pol snap-in pin;  
nominal voltage: 24 V DC 100 % ED, 120 mA  
used a power supply with stabilised voltage ;  
Please state the required version: "D", "F"

order-no. (Version D): effeff 819E32V92-40F9D

order-no. (Version F): effeff 819E32V92-40F9F

1 pce. \_\_\_\_\_

### 1.2. effeff connecting cable

fourteen-pin;

---

for model 809:  
backset 35 / 40 mm;  
with snap-in pin;  
length: approx. 9,5 m

order-no.: effeff 809ZBKAB04---00

1 pce. \_\_\_\_\_

**for the direct transfer of current from the door frame to the door**

### **1.3. effeff bridging cable**

for surface mounting,  
made of nickel-plated brass,  
with fixing lugs for screw mounting  
to door frame and door,  
spiral hose: I.D. = 7  
length: 30 cm

order-no.: effeff 10318-30-----00

1 pce. \_\_\_\_\_

**Further cable connector models find you in our safety lock catalog!**